



World Wide

Products >> UPS >> Back-UPS CS >> BK350EI

Back-UPS CS 350

Part Number : BK350EI

Estimated Retail Price : N/A

Availability : Eastern Europe : Middle East : Africa , Western Europe



Product Overview

- Description APC Back-UPS, 350VA/210W, Input 230V/ Output 230V, Interface Port USB
- General Features Addl Surge Protected Outlets , Audible Alarms , Auto Diagnostic Testing , Hot Swap Batteries , Internet FAX - modem - DSL protection , Lightning and Surge Protection , Modem Protection , Software , Status Indicator LED's , Unattended Shutdown , User replacable batteries , USB compatible
- Includes CD with software , User Manual , USB cable

Technical Specifications

Output

- Output power capacity 350 VA
- Output power capacity 210 Watts
- Nominal output voltage 230 V
- Waveform type Stepped approximation to a sinewave

- Output Connections (3)IEC 320 C13
- (1)IEC 320 C13 (Surge)
- (2)IEC Jumpers



Input

- Nominal input voltage 230 V
- Input frequency 50/60 Hz +/- 5 Hz (manual switch)
- Input Connection Type IEC-320-C14 inlet
- Input voltage range

Batteries

Typical backup time at half load	22.2 minutes
Battery type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	6 hour(s)
Replacement battery cartridge	(1) RBC2

Communications & Management

Interface port	USB
Optional Software	Click here to view other Software options .
Control panel	LED status display with On Line : On Battery : Replace Battery and Overload indicators
Audible alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rating	300 joules
Filtering	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449
Dataline protection	RJ-11 Modem/Fax/DSL protection (two wire single line)

Physical

Maximum height dimensions	3.60 inches (9.14 cm)
Maximum width dimensions	6.50 inches (16.51 cm)
Maximum depth dimensions	11.20 inches (28.45 cm)
Net weight	13.90 lbs (6.32 kg)
Shipping Weight	15.50 lbs (7.05 kg)
Shipping Height	7.00 inches (17.78 cm)
Shipping Width	9.50 inches (24.13 cm)
Shipping Depth	14.50 inches (36.83 cm)
Color	Beige

Environmental

Operating Environment	0 - 40 °C (32 - 104°F)
Operating Relative Humidity	0 - 95%
Operating Elevation	0-10000 feet (0-3000 m)
Storage Temperature	-15 - 45 °C (5 - 113°F)
Storage Relative Humidity	0 - 95%
Storage Elevation	0-50000 feet (0-15000 m)
Audible noise at 1 meter from surface of unit	40 dBA
Online thermal dissipation	19 BTU/hr

Conformance

Approvals

C-tick, CE, EN50091-1, EN50091-2, GOST, PCBC, VDE

Standard warranty

2 years repair or replace

|

|

|

|

|